

Revision: 09.08.2017

Printing date 09.08.2019

Version number 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RM 58 ASF
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Alkaline cleaner/ detergent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden

Postfach 160

D - 71349 Winnenden

Tel.: +49-7195-14-0 *Fax:* +49-7195-14-2212

www.karcher.com

· Further information obtainable from:

Department PCD-D Tel.: +49-7195-14-2548 Fax: +49-7195-14-3164 safetydata@karcher.com

· 1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



(Contd. of page 1)

Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

sodium hydroxide

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

 $P303 + P361 + P353 \ IF \ ON \ SKIN \ (or \ hair): \ Take \ off \ immediately \ all \ contaminated \ clothing. \ Rinse \ skin \ SKIN \ (or \ hair): \ Take \ off \ immediately \ all \ contaminated \ clothing.$

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

Cleaning agent

Mixture consisting of the following components.

· Dangerous components:		
CAS: 68891-38-3 NLP: 500-234-8	sodium lauryl ether sulfate Eye Dam. 1, H318; Skin Irrit. 2, H315; Aquatic	5-<10%
Reg.nr.: 01-2119488639-16-XXXX		
CAS: 68515-73-1	alkyl polyglucoside	5-<10%
NLP: 500-220-1	♦ Eye Dam. 1, H318	
Reg.nr.: 01-2119488530-36		
CAS: 1310-73-2	sodium hydroxide	2-<5%
EINECS: 215-185-5	Met. Corr.1, H290; Skin Corr. 1A, H314	
Index number: 011-002-00-6		
Reg.nr.: 01-2119457892-27-xxxx		

(Contd. on page 3)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

		(Cont	d. of page 2
CAS: 78330-20-8	fatty alcohol ethoxylate		1-5%
	🤣 Eye Dam. 1, H318; 🗘 Acute Tox. 4, H302		
· Regulation (EC) No 648/20	04 on detergents / Labelling for contents		
anionic surfactants, non-ionic surfactants		≥5	- <15%
perfumes (LIMONENE, CITRAL)			
· Additional information For	the wording of the listed hazard phrases refer to section	16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Involve doctor immediately.

Immediately remove any clothing soiled by the product.

· After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, powder or water spray. Fight larger fires with water spray.
- · For safety reasons unsuitable extinguishing agents Water with full jet.
- \cdot 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear fully protective suit.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

EH-



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with eyes and skin.

- $\cdot \textit{Information about fire and explosion protection:} \ \textit{No special measures required.}$
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Do not store together with acids.

Keep away from food, beverages and feed.

· Further information about storage conditions:

Protect from frost.

Keep receptacle tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A/P2.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

· Protection of hands:



Protective gloves.

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact gloves made of the following materials are suitable:
- * butyl rubber 0,7 mm, 480 min (EN 374)
- · As protection from splashes gloves made of the following materials are suitable:
- * nitril rubber 0,4 mm, 30 min (EN 374)
- · Eye protection:



Tightly sealed goggles (EN 166)

· Body protection:

Apron

Boots

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Fluid

Colour:

Yellow

· Odour:

citrus-like

· Odour threshold:

Not determined.

· pH-value at 20 °C:

13.1

(Contd. on page 6)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

	(Contd. of pag
pH-value 1 %:	12.0
Change in condition	
Melting point/freezing point:	-5 °C
Initial boiling point and boiling range	2: 100 °C
Flash point:	Not applicable
Flammability (solid, gaseous)	Not applicable.
Ignition temperature:	not applicable
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 20 °C:	23 hPa
Density at 20 °C:	1.064 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
dynamic at 20 °C:	12.5 mPas
kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
VOC (EC)	0.02 %
Solids content:	19.7 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity corresponds to 10.3
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Corrosive action on metals Reacts with strong acids

(Contd. on page 7)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

(Contd. of page 6)

Strong exothermic reaction with acids Reacts with light alloys to form hydrogen Corrodes aluminium

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

78330-20-8 fatty alcohol ethoxylate

Oral ATE 500 mg/kg (Rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

	12.1 10.0000	
· Aquatic toxici	· Aquatic toxicity:	
68891-38-3 sodium lauryl ether sulfate		
LC50	>10-100 mg/l (fish)	
EC50	>100 mg/l (bacteria)	
68515-73-1 al	68515-73-1 alkyl polyglucoside	
LC50/96 h	126 mg/l (fish)	
EC50/48 h	>100 mg/l (Daphnia magna)	
1310-73-2 sod	1310-73-2 sodium hydroxide	
LC50/96 h	125 mg/l (Gambusia affinis)	
EC50/48 h	76 mg/l (Daphnia magna)	

(Contd. on page 8)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

(Contd. of page 7)

EC50/15 min 22 mg/l (Photobacterium phosphoreum)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · COD-value: 350000
- · General notes:

The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

In compliance with the prescribed application parameters, the product does not lead to stable emulsions.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

· European waste catalogue

07 06 01* aqueous washing liquids and mother liquors

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

(Contd. on page 9)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

(Contd. of page 8)

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport informa	non
14.1 UN-Number ADR, IMDG, IATA	UN1824
14.2 UN proper shipping name ADR IMDG, IATA	1824 SODIUM HYDROXIDE SOLUTION SODIUM HYDROXIDE SOLUTION
14.3 Transport hazard class(es)	
ADR	
Class Label	8 (C5) Corrosive substances.
IMDG, IATA Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number: Segregation groups Stowage Category Segregation Code	Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 n Maximum net quantity per outer packaging: 1000



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

	(Contd. of page 9
	ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1824 SODIUM HYDROXIDE SOLUTION, 8 III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. A product information sheet can be provided if requested.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: PCD-D

· Contact:

Department PCD-D Tel.: +49-7195-14-2548 Fax: +49-7195-14-3164 safetydata@karcher.com

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)



Printing date 09.08.2019 Version number 4 Revision: 09.08.2017

Trade name: RM 58 ASF

(Contd. of page 10)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.

0.011-389.0

58/10-3

1.947

DII.