

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CARAMBA Profi High performance silicone spray(Aerosol)
- · Article number: 6103051, 6103251
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Auxiliary
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: CARAMBA CHEMIE GMBH & Co.KG Wanheimerstr. 334/336 47055 DUISBURG www.caramba.de
 Tel.: +49(0)203/7786 01
- **Further information obtainable from:** Abteilung Produktsicherheit Sicherheitsdatenblaetter@caramba.de

SECTION 2: Hazards identification

[.] 2.1 Classification of the substance or mixture

 Classification acc 	cation according to Regulation (EC) No 1272/2008		
Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.	
Skin Irrit. 2	H315	Causes skin irritation.	
STOT SE 3	H336	May cause drowsiness or dizziness.	
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.	
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.	

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

• Hazard pictograms



GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

- Hazard statements
- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.

^{· 1.4} Emergency telephone number: Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

... das wirkt!

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

(Contd. of page 1)

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% n-hexane	10-25%	
	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336		
CAS: 106-97-8	Butane	10-25%	
EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	Flam. Gas 1, H220; Press. Gas C, H280		
Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	10-25%	
	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336		
CAS: 74-98-6	Propane	10-25%	
EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	Flam. Gas 1, H220; Press. Gas L, H280		
CAS: 75-28-5	Isobutane	1-2.5%	
EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	Flam. Gas 1, H220; Press. Gas C, H280		
CAS: 110-54-3	n-hexane	<1%	
EINECS: 203-777-6	Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336		
CAS: 110-82-7	Cyclohexane	<1%	
EINECS: 203-806-2 Reg.nr.: 01-2119463273-41	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336		

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Page 2/8





Page 3/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

(Contd. of page 2)

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

• Information about fire - and explosion protection: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB -



Page 4/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

(Contd. of page 3)

8.1 Control parameters		
Ingredients with limit values that rec	guire monitoring at the workplace:	
106-97-8 Butane (10-25%)	12	
WEL Short-term value: 1810 mg/m ³ , 7 Long-term value: 1450 mg/m ³ , 6 Carc (if more than 0.1% of buta-	00 ppm	
110-54-3 n-hexane (<1%)		
WEL Long-term value: 72 mg/m ³ , 20 p	m	
110-82-7 Cyclohexane (<1%)	····	
WEL Short-term value: 1050 mg/m³, 3 Long-term value: 350 mg/m³, 10	300 ррт 0 ррт	
Personal protective equipment: General protective and hygienic mea Keep away from foodstuffs, beverages Immediately remove all soiled and cont Wash hands before breaks and at the	and feed. taminated clothing	
Do not inhale gases / fumes / aerosols. Respiratory protection: Not required. Protection of hands: Solvent resistan Material of gloves Nitrile rubber, NBR	t gloves	
Do not inhale gases / fumes / aerosols. Respiratory protection: Not required. Protection of hands: Solvent resistan	It gloves alue for the permeation: Level ≥ 480	
Do not inhale gases / fumes / aerosols. Respiratory protection: Not required. Protection of hands: Solvent resistan Material of gloves Nitrile rubber, NBR Penetration time of glove material V Eye protection: Safety glasses	It gloves alue for the permeation: Level ≥ 480 mical properties	
Do not inhale gases / fumes / aerosols. Respiratory protection: Not required. Protection of hands: Solvent resistan Material of gloves Nitrile rubber, NBR Penetration time of glove material V Eye protection: Safety glasses SECTION 9: Physical and cher 9.1 Information on basic physical and General Information Appearance: Form: Colour: Odour:	alue for the permeation: Level ≥ 480 mical properties ad chemical properties Aerosol Clear Fruit-like	
Do not inhale gases / fumes / aerosols. Respiratory protection : Not required. Protection of hands : Solvent resistan Material of gloves Nitrile rubber, NBR Penetration time of glove material V Eye protection : Safety glasses SECTION 9: Physical and cher 9.1 Information on basic physical and General Information Appearance: Form: Colour: Odour: Odour threshold:	alt gloves alue for the permeation: Level ≥ 480 mical properties ad chemical properties Aerosol Clear Fruit-like Not determined. Not determined. Undetermined.	

- · Flash point:
- Flammability (solid, gas):
- Decomposition temperature:
- Auto-ignition temperature:
- · Explosive properties:
- · Explosion limits: Lower: Upper:

mixtures are possible. Not determined. Not determined.

Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapour

Not applicable.

Not determined.

Page 5/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

		(Contd. of page 4
Vapour pressure:	Not determined.	
Density at 20 °C:	0.68 g/cm³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.



... das wirkt!

Page 6/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

• Ecotoxical effects: • Remark: Toxic for fish

· General notes:

· Additional ecological information:

Version number 12

Revision: 06.03.2019

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

(Contd. of page 5)

Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. · 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available. **SECTION 13: Disposal considerations** · 13.1 Waste treatment methods · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system. · Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations. **SECTION 14: Transport information** · 14.1 UN-Number · ADR, IMDG, IATA UN1950 14.2 UN proper shipping name · ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS ·IMDG AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane), MARINE POLLUTANT ·IATA AEROSOLS, flammable 14.3 Transport hazard class(es) · ADR 2 5F Gases. · Class · Label 2.1 ·IMDG · Class 2.1 · Label 2.1 (Contd. on page 7) GB



Page 7/8



according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

	(Contd. of page 6)
*	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Hydrocarbons, C6, isoalkanes, <5% n-hexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
· Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
· EMS Number:	F-D,S-U SW1 Protected from sources of heat.
Stowage Code	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
 14.7 Transport in bulk according to Annex II Marpol and the IBC Code 	
· Transport/Additional information:	
ADR	
• Excepted quantities (EQ):	EO
· Limited quantities (LQ)	1L
· Transport category	2
Tunnel restriction code	D
· UN "Model Regulation":	UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Please note TRGS 510.

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.



... das wirkt!

Page 8/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.03.2019

Version number 12

Revision: 06.03.2019

Trade name: CARAMBA Profi High performance silicone spray(Aerosol)

(Contd. of page 7)

· Relevant phrases	
H220 Extremely flammable gas.	
H225 Highly flammable liquid and vapour.	
H280 Contains gas under pressure; may explode if heated.	
H304 May be fatal if swallowed and enters airways.	
H315 Causes skin irritation.	
H336 May cause drowsiness or dizziness.	
H361f Suspected of damaging fertility.	
H373 May cause damage to organs through prolonged or repeated exposure.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
H411 Toxic to aquatic life with long lasting effects.	
Abbreviations and acronyms:	
Flam. Gas 1: Flammable gases – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas C: Gases under pressure – Compressed gas	
Press. Gas L: Gases under pressure – Liquefied gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
• * Data compared to the previous version altered.	
	GB

