

Page 1/10

Fax: 0049-(0)7223-284-245

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU plus endfest 300 (Härter)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU BOSTIK S.p.A. - Via G.B. Pirelli, 19 - 20124 Milano

Tel. +39.02.6775.08 Fax +39.02.6775.481

mail@uhubostik.it

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

email: sds@uhu.boltongroup.com

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

Hazard pictograms



GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine amine, polyethylenepoly-,triethylenetetramine fraction

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Mixture of substances listed below with nonhazardous additions. Adhesive

· Dangerous components:				
CAS: 10563 EINECS: 23		N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine ♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Skin Sens. 1, H317	2.5-10%	
CAS: 90640 EINECS: 29 Reg.nr.: 01-	2-588-2	amine, polyethylenepoly-,triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5-10%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

EU-EN

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment neededNo further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Water spray

Carbon dioxide

Foam

Fire-extinguishing powder

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CÓ)

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 3)

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

- · Storage class: 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Recommended filter device for short term use: Combination filter A-P1
- · Protection of hands:

Rubber gloves

(Contd. on page 5)

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

Material of gloves

Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)

Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection:



Safety glasses

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:

Form: Fluid
Colour: Yellow
Odour: Amine-like
Odour threshold: Not determined.

• **pH-value at 20 °C:** 12 (1:1 in H2O)

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: ~278 °C

(Contd. on page 6)

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

	(Contd. of page
· Flash point:	>100 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	335 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not determined.
Density at 20 °C: Relative density Vapour density Evaporation rate	0.95 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	32500 mPas Not determined.
Solvent content: VOC (EC)	0.00 %
Solids content: 9.2 Other information	84.2 % All relevant physical data were determined for th mixture. All non determined data are not measurably on the relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

EU-EN

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

90640-67-8 amine, polyethylenepoly-,triethylenetetramine fraction

Oral LD50 2500 mg/kg (rat)
Dermal LD50 805 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

Disposal must be made according to official regulations.

(Contd. of page 7)

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name	
ADR IMDG, IATA	2735 POLYAMINES, LIQUID, CORROSI N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropa 1,3-diamine, amine, polyethylenepo triethylenetetramine fraction) POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminopropyl)-N,N-dimethylpropane-1 diamine, amine, polyethylenepo triethylenetetramine fraction)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
<u> </u>	
14.6 Special precautions for user Danger code (Kemler):	Warning: Corrosive substances. 80
EMS Number:	F-A.S-B
Segregation groups	Alkalis
oogiogadon groupo	A
Stowage Category	
Stowage Category Segregation Code	SG35 Stow "separated from" SGG1-acids

EU-EN

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

	(Contd. of page 8
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE N.O.S. (N'-(3-AMINOPROPYL)-N, N DIMETHYLPROPANE-1,3-DIAMINE, AMINE POLYETHY LENEPOLY ,TRIETHYLENETETRAMINE FRACTION), 8, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: UHU QESH
- · Contact: Dr. C. Hanf
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

(Contd. of page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.07.2019 Version number 32 Revision: 05.07.2019

Trade name: UHU plus endfest 300 (Härter)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

FU-FN