



Artikelbezeichnung	Art.-Nr.	max. empfohlene zentr. Zuglast für MS-L 27/18	max. empfohlene zentr. Zuglast für MS-L 28/30	max. empfohlener Querkzug	Anzugsdrehmoment
		N_{empf} [kN]	N_{empf} [kN]	V_{empf} [kN]	T_{inst} [Nm]
FHS CLIX 8 x 30	079621	1.7	2.0	0.2	5
FHS CLIX 8 x 40	079622	1.7	2.0	0.2	5
FHS CLIX 8 x 60	079624	1.7	2.0	0.2	5
FHS CLIX 8 x 80	079626	1.7	2.0	0.2	5
FHS CLIX 8 x 100	079628	1.7	2.0	0.2	5
FHS CLIX 10 x 30	079635	2.0	2.2	0.3	8
FHS CLIX 10 x 40	079636	2.0	2.2	0.3	8
FHS CLIX 10 x 60	079637	2.0	2.2	0.3	8
FHS CLIX 10 x 100	505554	2.0	2.2	0.3	8
FHS CLIX-N M 8 x 90	079605	1.7	2.0	0.2	5
FHS CLIX-N M 8 x 140	079606	1.7	2.0	0.2	5
FHS CLIX-N M 8 x 190	079607	1.7	2.0	0.2	5