

Printing date 20.04.2015

Version number 302

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision: 20.04.2015

· 1.1 Product identifier · Trade name: 2K-Flüssig-Metall E-COLL · Article number: 4317784465007, 4317784465014 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Application of the substance / the mixture Adhesives \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany Tel. +49 202 6096-0 e-mail: sdb@ede.de • Further information obtainable from: Product safety department • 1.4 Emergency telephone number: Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS09 environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS07 GHS09 · Signal word Warning · Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. (Contd. on page 2) GB



Version number 302

Revision: 20.04.2015

Trade name: 2K-Flüssig-Metall E-COLL

	(Contd. of page 1)
P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P33	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional inform	nation:
Contains epoxy c	onstituents. May produce an allergic reaction.
· 2.3 Other hazard	S
• Results of PBT a	nd vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	50-100%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised)	10-25%
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	2.5-10%

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air.
- Seek medical treatment in case of complaints.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

- If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:
- Rinse out mouth and then drink plenty of water.
- Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

GB



Version number 302

Revision: 20.04.2015

Trade name: 2K-Flüssig-Metall E-COLL

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:
- Store away from foodstuffs.

Store away from oxidising agents.

- Do not store together with acids.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. of page 2)



Version number 302

Revision: 20.04.2015

(Contd. of page 3)

Trade name: 2K-Flüssig-Metall E-COLL

· Protection of hands:



Protective gloves

- **Material of gloves** Nitrile rubber, NBR
- Recommended thickness of the material: $\geq 0.4 \text{ mm}$
- \cdot Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- \cdot Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

Colour:Silver greyOdour:MildOdour threshold:Not determined.pH-value:Not determined.Change in conditionUndetermined.Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:>200 °CDecomposition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.	Appearance: Form:	Pasty	
Odour:MildOdour threshold:Not determined.pH-value:Not determined.Change in conditionUndetermined.Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Vapour pressure:Not determined.Vapour pressure:Not determined.Vapour pressure:Not determined.Vapour densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Solubility in / Miscibility withHitelemined.		5	
Odour threshold:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Flash point:Not applicable.Ignition temperature:>200 °CDecomposition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:Not determined.Vapour pressure:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³ 		· ·	
Change in condition Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:>200 °CDecomposition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower:Not determined.Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³ Relative densitySolubility in / Miscibility withNot determined.			
Meliting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:>200 °CDecomposition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Solubility in / Miscibility with	pH-value:	Not determined.	
Boiling point/Boiling range:Undetermined.Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:>200 °CDecomposition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Vot determined.Lower:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Solubility in / Miscibility with	Change in condition		
Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Ignition temperature:>200 °CDecomposition temperature:>200 °CSelf-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Solubility in / Miscibility with		Undetermined.	
Flammability (solid, gaseous): Not applicable. Ignition temperature: Decomposition temperature: Decomposition temperature: >200 °C Self-igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Ignet: Lower: Not determined. Upper: Not determined. Vapour pressure: Not determined. Density at 20 °C: 1.4 g/cm³ Relative density Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with Not determined.	Boiling point/Boiling range:	Undetermined.	
Ignition temperature: >200 °C Decomposition temperature: >200 °C Self-igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Image: Not determined. Lower: Not determined. Vapour pressure: Not determined. Density at 20 °C: 1.4 g/cm ³ Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined.	Flash point:	Not applicable.	
Self-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Solubility in / Miscibility with	Flammability (solid, gaseous):	Not applicable.	
Self-igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Solubility in / Miscibility with	Ignition temperature:		
Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm ³ Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Solubility in / Miscibility with	Decomposition temperature:	>200 °C	
Explosion limits: Lower: Not determined. Upper: Not determined. Vapour pressure: Not determined. Density at 20 °C: 1.4 g/cm ³ Relative density Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with Not determined.	Self-igniting:	Product is not selfigniting.	
Lower: Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with	Danger of explosion:	Product does not present an explosion hazard.	
Upper:Not determined.Vapour pressure:Not determined.Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with	Explosion limits:		
Vapour pressure: Not determined. Density at 20 °C: 1.4 g/cm ³ Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Value	Lower:		
Density at 20 °C:1.4 g/cm³Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility with	Upper:	Not determined.	
Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility withImage: Comparison of the second	Vapour pressure:	Not determined.	
Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.Solubility in / Miscibility withImage: Comparison of the second	Density at 20 °C:	1.4 g/cm ³	
Evaporation rate Not determined. Solubility in / Miscibility with		•	
Solubility in / Miscibility with	Vapour density	Not determined.	
	Evaporation rate	Not determined.	
	Solubility in / Miscibility with		
	water:	Not miscible or difficult to mix.	



Version number 302

Revision: 20.04.2015

Trade name: 2K-Flüssig-Metall E-COLL

		(Contd. of page 4)
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOCV (CH)	0.0 %	
Solids content:	30.0 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.
- \cdot **10.4 Conditions to avoid** No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitisation: Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Toxic for fish
- \cdot Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Toxic for aquatic organisms
- Also poisonous for fish and plankton in water bodies.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 6)



Version number 302

Revision: 20.04.2015

Trade name: 2K-Flüssig-Metall E-COLL

(Contd. of page 5)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) •IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT •IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) •IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) •IA3 Transport hazard class(es) •ADR •ADR § (M6) Miscellaneous dangerous substances and articles. • Label 9 • IMDG, IATA § • Label 9 • IA4. Packing group 9 • ADR, IMDG, IATA III • 14.5 Environmental hazards: Product contains environmentally hazardous substances	SECTION 14: Transport informe	ntion
• ADR UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) • IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT • IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) • IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) • IA3 Transport hazard class(es) • • ADR • • Class 9 (M6) Miscellaneous dangerous substances and articles. • Label 9 • IMDG, IATA 9 • IMDG, IATA 9 • Class 9 Miscellaneous dangerous substances and articles. • Label 9 • IA4 Packing group III • ADR, IMDG, IATA III • ADR, IMDG, IATA III • ADR, IMDG, IATA III • Special marking (ADR): Symbol (fish and tree) • Special marking (IATA): Symbol (fish and tree)		UN3082
· IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT · IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) · 14.3 Transport hazard class(es) · · ADR · · Class 9 (M6) Miscellaneous dangerous substances and articles. · Label 9 · IMDG, IATA 9 · IAJR factor 9 · IAJR factor 9 · IMDG, IATA 9 · IMDG, IATA 9 · IAJR factor 9 · IAJR factor 9 · IMDG, IATA 9 · IAJR factor 9 · IABel 9 · IAJR factor 9 · IABel 9 · IABel 9 · IABE 9		UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average
 IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) I4.3 Transport hazard class(es) ADR ADR Class Label 9 (M6) Miscellaneous dangerous substances and articles. 9 IMDG, IATA IMDG, IATA IA4 Packing group ADR, IMDG, IATA III I4.5 Environmental hazards: Product contains environmentally hazardous substances. reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Marine pollutant: Special marking (ADR): Symbol (fish and tree) Symbol (fish and tree) 	·IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular
 ADR . ADR . ADR . ADR . Class . Label . MDG, IATA . ADR . Class . Class . P Miscellaneous dangerous substances and articles. . 9 . Class . 9 . Class . 9 Miscellaneous dangerous substances and articles. . 9 . Class . 9 Miscellaneous dangerous substances and articles. . 9 . 14.4 Packing group . ADR, IMDG, IATA . 14.5 Environmental hazards: . Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) . Marine pollutant: . Special marking (ADR): . Symbol (fish and tree) . Symbol (fish and tree) . Symbol (fish and tree) 	·IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular
• Class 9 (M6) Miscellaneous dangerous substances and articles. • Label 9 • IMDG, IATA 9 • Class 9 Miscellaneous dangerous substances and articles. • Class 9 Miscellaneous dangerous substances and articles. • Class 9 Miscellaneous dangerous substances and articles. • Label 9 • Class 9 Miscellaneous dangerous substances and articles. • Label 9 • Alek 9 • 14.4 Packing group 111 • 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) • Marine pollutant: Yes • Special marking (ADR): Symbol (fish and tree) • Special marking (IATA): Symbol (fish and tree)	· 14.3 Transport hazard class(es)	
Label 9 · IMDG, IATA • • IMDG, IATA • • IMDG, IATA • • Import • • • Class 9 Miscellaneous dangerous substances and articles. • Label 9 • 14.4 Packing group 9 • ADR, IMDG, IATA III • 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) • Marine pollutant: Yes • Special marking (ADR): Symbol (fish and tree) • Special marking (IATA): Symbol (fish and tree)	· ADR	
Label 9 · IMDG, IATA • • IMDG, IATA • • IMDG, IATA • • Import • • • Class 9 Miscellaneous dangerous substances and articles. • Label 9 • 14.4 Packing group 9 • ADR, IMDG, IATA III • 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) • Marine pollutant: Yes • Special marking (ADR): Symbol (fish and tree) • Special marking (IATA): Symbol (fish and tree)		
• Class 9 Miscellaneous dangerous substances and articles. • Label 9 • 14.4 Packing group 9 • ADR, IMDG, IATA III • 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy reside (number average molecular weight ≤ 700) • Marine pollutant: Yes • Special marking (ADR): Symbol (fish and tree) • Special marking (IATA): Symbol (fish and tree)		
· Label 9 · 14.4 Packing group	· IMDG, IATA	
· Label 9 · 14.4 Packing group		
· ADR, IMDG, IATA III · 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) · Marine pollutant: Yes Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): Symbol (fish and tree)		
• Marine pollutant: reaction product: bisphenol-A-(epichlorhydrin) epoxy resing (number average molecular weight ≤ 700) • Special marking (ADR): Yes • Special marking (IATA): Symbol (fish and tree)		111
• Marine pollutant: Yes • Special marking (ADR): Symbol (fish and tree) • Special marking (IATA): Symbol (fish and tree)	· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < 700)
Special marking (ADR):Symbol (fish and tree)Special marking (IATA):Symbol (fish and tree)	• Marine pollutant:	Yes
		Symbol (fish and tree)
	· Special marking (IATA):	Symbol (fish and tree)



Version number 302

Revision: 20.04.2015

Trade name: 2K-Flüssig-Metall E-COLL

	(Contd. of page
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
· Danger code (Kemler):	90
· EMS Number:	F-A,S-F
· 14.7 Transport in bulk according to Anne	x II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· <i>ADR</i>	
\cdot Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
• Tunnel restriction code	E
· IMDG	
\cdot Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN3082, ENVIRONMENTALLY HAZARDOU
-	SUBSTANCE, LIQUID, N.O.S. (reaction product
	bisphenol-A-(epichlorhydrin) epoxy resin (number averag
	molecular weight \leq 700)), 9, III

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H228 Flammable solid. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. · Contact: sdb@ede.de · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweis (Swiss Ordinance on volatile organic compounds) Flam. Sol. 1: Flammable solids, Hazard Category 1 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2